

GREZALL ML-1

GREZALL ML-1 is a premium quality, lithium complex, extreme pressure lubricating grease. It has excellent shear stability and provides long life at high temperatures. **GREZALL ML-1** contains molybdenum disulfide lubricants that lower the coefficient of friction under conditions of high temperatures and heavy loads. It is suitable for use in central grease lubricating systems.

PHYSICAL CHARACTERISTICS

<u>TEST METHOD</u>	<u>DESCRIPTION</u>	<u>RESULTS</u>
	NLGI Grade	1
ASTM D 217	Worked Penetration, 60 Strokes	310 – 340
ASTM D 2265	Dropping Point, °F.	500 min.
ASTM D 445	Oil Viscosity, cST @ 40°C.	128 – 150
ASTM D 2270	Viscosity Index	95 min.
	Color	Grey
	Appearance	Smooth
ASTM D 2509	Timken Load, Lbs.	50 min.
ASTM D 1743	Rust Prevention	Pass
ASTM D 942	Oxidation Stability 100 Hrs. PSI	5 maximum

TECHNICAL SUPPORT

TOWER wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and **TOWER's** assistance, however, are not substitute for your own testing and evaluation.

02169/111