



## **RUSTBEAT 605-A**

**RUSTBEAT 605-A** is a specialty rust preventive compounded with highly effective corrosion inhibitors to give outstanding protection to ferrous metals. **RUSTBEAT 605-A** can be used for a wide variety of applications requiring indoor storage for extended periods of time. It will leave a light oily residue on the surface of the metal.

### **USAGE**

**RUSTBEAT 605-A** is a straight oil and can be applied by spray, brush, dip tank or recirculating spray methods. It is typically used when up to nine month of indoor storage protection is required. The oil residue left by **RUSTBEAT 605-A** is typically compatible with motor oils, transmission fluid, hydraulic fluid, and other lubricating oils. It is easy to remove in conventional cleaning systems.

### **PHYSICAL CHARACTERISTICS**

Density	0.90 g/ml 7.5 lbs/gal
Appearance	Dark Amber Liquid
Odor	Bland Petroleum
Flash Point (COC)	Greater than 290°F
Film	Oily
Coverage	1100 Square Feet per Gallon
Indoor Protection	Approximately 9 months
Viscosity	Typically 70 SUS @ 100°F.

### **BENEFITS**

- **Safe To Use**
- **Provides Up To Nine Months Indoor Protection**
- **Light Oily Protective Film**

### **TECHNICAL SUPPORT**

**TOWER** wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and **TOWER's** assistance, however, are not a substitute for your own testing and evaluation. 05035