



TOWER CF-912

TOWER CF-912 is a custom blended metal working compound specifically designed for in-die tapping operations. **CF-912** utilizes unique chlorine-free chemistry. It is compounded with two types of wetting agents, extreme pressure additives and a mist suppressant. Frequently, **CF-912** is used as a combination die lubricant and tapping compound. **CF-912** is designed for use on ferrous metals, galvanized steels, aluminum and stainless steel.

USAGE

TOWER CF-912 should be used as supplied from the drum. **TOWER CF-912** can be applied in minimal amounts through JET-SET® airless spray, drip, roller coater, or in recirculating systems.

PHYSICAL CHARACTERISTICS

Density	.90 g/ml 7.5 lbs./gal.
Appearance	Dark Amber Liquid
Odor	Mild Petroleum Odor
Viscosity	Typically 110 SUS @ 100°F

BENEFITS

- **Contains No Hazardous Ingredients**
- **Provides Excellent In-Process Rust Protection**
- **Cleans Easily in Aqueous Cleaners**
- **Designed for Heavy Duty Operations**
- **Exhibits Excellent Surface Wetting & Anti-Galling Characteristics**
- **Has excellent Operator Acceptance**

TECHNICAL SUPPORT

TOWER OIL & TECHNOLOGY Co. wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and TOWER OIL & TECHNOLOGY Co.'s assistance, however, are not a substitute for your own testing and evaluation.

00145