



TOWERDRAW 9355-TD

TOWERDRAW 9355-TD is a compounded petroleum-based product formulated for use as a die lubricant in metal stamping and drawing operations. It has unique wetting and flushing properties in combination with extreme pressure additives. A minimal film remains after drying which provides in-process corrosion protection. **TOWERDRAW 9355-TD** has good weld through characteristics.

USAGE

TOWERDRAW 9355-TD should be used as supplied. It can be applied in minimal amounts through airless spray, drip, or roller coater systems. **TOWERDRAW 9355-TD** can be easily removed by aqueous cleaners.

PHYSICAL CHARACTERISTICS

Density	0.82 g/ml 6.9 lbs/gal
Appearance	Pale Yellow Liquid
Odor	Bland Solvent
Viscosity	Water-like
Flash Point	Greater Than 140°F, TCC

BENEFITS

- **Contains No Hazardous Ingredients**
- **Provides Good In-process Corrosion Protection**
- **Can Be Welded Through Without Cleaning**
- **Cleans Easily in Aqueous Cleaners**
- **Exhibits Excellent Surface Wetting & Anti-Galling Characteristics**
- **Receives Excellent Operator Acceptance**

TECHNICAL SUPPORT

TOWER wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and **TOWER's** assistance, however, are not a substitute for your own testing and evaluation.

03282