



## **TOWERDRAW 9560-TD**

**TOWERDRAW 9560-TD** is a petroleum-based product formulated for heavy-duty metal forming operations. It has unique wetting properties in combination with sulfur chlorinated extreme pressure additives. The chemistry of **TOWERDRAW 9560-TD** is suitable for tough stainless steel forming operations and for use on high strength ferrous metals. **TOWERDRAW 9560-TS** is designed for transfer press operations and other multi-stage forming, drawing and deep drawing applications.

### **USAGE**

**TOWERDRAW 9560-TD** should be used as supplied from the drum. **TOWERDRAW 9560-TD** can be applied in minimal amounts through airless spray, drip, roller coater, or in recirculating systems.

### **PHYSICAL CHARACTERISTICS**

Density	1.02 g/ml 8.51 lbs./gal.
Appearance	Clear Amber Liquid
Odor	Bland Petroleum Odor
Viscosity	650 SUS @ 100°F (typical)

### **BENEFITS**

- **Contains No Hazardous Ingredients**
- **Provides Excellent In-Process Rust Protection**
- **Cleans Easily in Aqueous Cleaners**
- **Designed for Heavy Duty Operations**
- **Exhibits Excellent Surface Wetting & Anti-Galling Characteristics**
- **Offers Low Odor Characteristics at High Temperatures**
- **Receives Excellent Operator Acceptance**

### **TECHNICAL SUPPORT**

**TOWER OIL & TECHNOLOGY Co.** wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and TOWER OIL & TECHNOLOGY Co.'s assistance, however, are not a substitute for your own testing and evaluation.

99166